



SPACE 1.5

Technical specification

	Description	Features
EXTERIOR	Width x Height x Depth (cm / in)	145x229x110 / 57x90x43
INTERIOR	Width x Height x Depth (cm / in)	125x205x101 / 49x81x40
WEIGHT	kg / lb	428 / 944
WEIGHT WITH CRATE	kg / lb	555 / 1224
SOUND INSULATION	Airborne sound insulation R' _w =43 dB	Measurements based on ISO 16283-1 and ISO 23351-1
EXTERIOR	Laminated exterior panels and cover trims	Medical grade antibacterial laminate
GLASS	Sound Control laminated glass	Sound insulation STC 40 dB
SOLID ELEMENTS	EchoFree panel - sandwich element of birch plywood, ecological foam and acoustic felt	Sound insulation STC 49 dB Acoustic absorption class A
ROOF	EchoFree panel - sandwich element of birch plywood, ecological foam and acoustic felt	Sound insulation STC 45 dB Acoustic absorption Class A
FLOOR	Sandwich element of birch plywood, acoustic wool	Acoustic absorption Class B
CARPET	Antistatic and stain resistant low loop pile carpet for public spaces, EN 1307	Flammability B _{fl} -s1
DOOR HANDEDNESS	Right-handed door	
AIR VENTILATION	Low consumption air circulation system (stand by 3,4W; in operation 6,8W)	Air circulation speed is more than 50 l/s
TABLE	Optional: Fixed height / electrically adjustable / no table	Antibacterial laminate
SEAT	Optional: Ergonomic sofa / No seat	Color customizable
CONNECTIONS	AC outlet(100-240V) + USB A/C Ethernet port (optional) Power cord length 5 m	The availability of connections depends on the region
LIGHTING	LED lighting (13,4W, 4000 K, 1800 lm)	Low consumption, energy-efficient
CASTERS	For easy relocation	Hidden. Can be activated any time
ADJUSTABLE LEGS	For levelling	Levelling from inside the booth
INDOOR AIR QUALITY	Indoor Advantage™ Gold	Indoor Air Quality Certified to SCS-EC10.3-2014 v4.0
GENERAL SAFETY	UL 962 listed	Standard for Safety for Household and Commercial Furnishings

