



SPACE 1

Technical specification

	Description	Features
EXTERIOR	Width x Height x Depth (cm / in)	110x229x110 / 43x90x43
INTERIOR	Width x Height x Depth (cm / in)	90x205x101 / 35x81x40
WEIGHT	kg / lb	370 / 816
WEIGHT WITH CRATE	kg / lb	500 / 1102
SOUND INSULATION	Airborne sound insulation $R'w=40$ dB Speech level reduction $D_{s,A}=30,5$ dB	Measurements based on ISO 16283-1 and ISO 23351-1
EXTERIOR	Laminated exterior panels and cover trims	Medical grade antibacterial laminate
GLASS	Sound Control laminated glass	Sound insulation STC 40 dB
SOLID ELEMENTS	EchoFree panel - sandwich element of birch plywood, ecological foam and acoustic felt	Sound insulation STC 49 dB Acoustic absorption class A
ROOF	EchoFree panel - sandwich element of birch plywood, ecological foam and acoustic felt	Sound insulation STC 45 dB Acoustic absorption Class A
FLOOR	Sandwich element of birch plywood, acoustic wool	Acoustic absorption Class B
CARPET	Antistatic and stain resistant low loop pile carpet for public spaces, EN 1307	Flammability $B_{fl}-s1$
DOOR HANDEDNESS	Right- or left-handed door	Door handedness can be chosen
TABLE	Antibacterial laminate / painted steel	Magnetic surface
AIR VENTILATION	Low consumption air circulation system (stand by 1,7W; in operation 3,4W)	Air circulation speed is more than 27 l/s
SEAT	Optional: Integrated stool / HAY Revolver stool / No seat	Color customizable, Turnable 360 degrees
CONNECTIONS	AC outlet(100-240V) + USB A Ethernet port (optional) Power cord length 5 m	The availability of connections depends on the region
LIGHTING	LED lighting (6,7W, 4000 K, 900 lm)	Low consumption, energy-efficient
CASTERS	For easy relocation	Hidden. Can be activated any time
ADJUSTABLE LEGS	For levelling	Levelling from inside the booth
INDOOR AIR QUALITY	Indoor Advantage™ Gold	Indoor Air Quality Certified to SCS-EC10.3-2014 v4.0
GENERAL SAFETY	UL 962 listed	Standard for Safety for Household and Commercial Furnishings

